


High Reliability Power Inductors ML512PYA



- High temperature materials allow operation in ambient temperatures up to 155°C
- Passes vibration testing to 80 G and shock testing to 1000 G
- Exceptionally low DCR – 1.59 mOhm
- Soft saturation makes them ideal for VRM/VRD applications.

Terminations Tin-silver (96.5/3.5) over copper.

Core material Composite

Weight 0.6 – 0.7 g

Ambient temperature –55°C to +105°C with Irms current

Maximum part temperature +155°C (ambient + temp rise).

Storage temperature Component: –55°C to +155°C.

Tape and reel packaging: –55°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Enhanced crush-resistant packaging 400/7" reel

Plastic tape: 16 mm wide, 0.3 mm thick, 12 mm pocket spacing, 3.12 mm pocket depth

Part number ¹	Inductance ² ±20% (µH)	DCR (mOhms) ³		SRF (MHz) ⁴		Isat (A) ⁵	Irms (A) ⁶	
		typ	max	min	typ		20°C rise	40°C rise
ML512PYA181MLZ	0.18	1.59	1.75	113	141	39	18.0	24.0
ML512PYA331MLZ	0.33	2.30	2.53	71	89	30	15.0	18.8
ML512PYA561MLZ	0.56	3.01	3.31	49	61	29	12.0	16.5
ML512PYA102MLZ	1.0	5.62	6.18	40	50	23	9.8	13.5
ML512PYA122MLZ	1.2	6.82	7.50	34	43	22	9.0	12.0
ML512PYA182MLZ	1.8	9.57	10.52	27	34	18.2	7.6	10.5
ML512PYA222MLZ	2.2	12.70	13.97	24	30	15.9	5.3	7.5
ML512PYA332MLZ	3.3	19.92	20.81	21	26	12.2	4.5	6.0

1. When ordering, please specify **testing** code:

ML512PYA332MLZ

Testing: Z = Unscreened

H = Group A screening per Coilcraft CP-SA-10001

All screening performed to the document's latest revision

2. Inductance tested at 100 kHz, 0.1 Vrms, 0 Adc.
3. DCR measured on a micro-ohmmeter.
4. SRF measured using an Agilent/HP 4395A or equivalent.
5. Typical dc current at which the inductance drops 30% from its value without current.
6. Typical current that causes the specified temperature rise from 25°C ambient.
7. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.









Irms Testing

Irms testing was performed on a 0.060" thick pcb with 4 oz. copper traces optimized to minimize additional temperature rise.

Temperature rise is highly dependent on many factors including pcb land pattern, trace size, and proximity to other components. Therefore temperature rise should be verified in application conditions.

ML512PYA Series

L vs Current



1102 Silver Lake Road
Cary, IL 60013
Phone 800-981-0363

© Coilcraft, Inc. 2017






Fax 847-639-1508
Email cps@coilcraft.com
www.coilcraft-cps.com

Document ML800-2 Revised 05/28/17

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specifications subject to change without notice. Please check our web site for latest information.

ML512PYA Series

L vs Frequency



Suggested Land Pattern

Dash number	Terminal thickness (typ) (in / mm)
-181	0.0106 / 0.27
-331	0.0106 / 0.27
-561	0.0106 / 0.27
-102	0.0071 / 0.18
-122	0.0071 / 0.18
-182	0.0059 / 0.15
-222	0.0047 / 0.12
-332	0.0039 / 0.10

Dimensions are in $\frac{\text{inches}}{\text{mm}}$