

# High-Reliability Power Inductors MS566PNB



- High current, low DCR shielded power inductors
- High temperature materials allow operation in ambient temperatures up to 155°C.
- Tin-lead (Sn-Pb) terminations for the best possible board adhesion

**Core material** Ferrite

**Terminations** Tin-lead (63/37) over tin over nickel over phos bronze.

**Weight:** 2.3 g – 2.5 g

**Ambient temperature** –55°C to +105°C with Irms current

**Maximum part temperature** +155°C (ambient + temp rise).

**Storage temperature** Component: –55°C to +155°C.  
Packaging: –55°C to +80°C

**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)

**Enhanced crush-resistant packaging** 200/7" reel

Plastic tape: 24 mm wide, 0.35 mm thick, 16 mm pocket spacing, 4.7mm pocket depth

Part number <sup>1</sup>	Inductance <sup>2</sup> (µH)	DCR <sup>3</sup> (mOhms)		SRF (MHz) <sup>4</sup>		Isat (A) <sup>5</sup>			Irms (A) <sup>6</sup>	
		typ	max	min	typ	10% drop	20% drop	30% drop	20°C rise	40°C rise
MS566PNB102MSZ	1.0±20%	5.6	6.3	70.0	100	18.14	20.64	22.24	6.00	8.00
MS566PNB152MSZ	1.5±20%	8.7	9.7	60.0	85.0	14.06	15.90	17.08	5.80	7.80
MS566PNB272MSZ	2.7±20%	10.3	11.5	49.0	70.0	11.66	13.16	14.16	5.00	6.80
MS566PNB332MSZ	3.3±20%	15.1	16.8	46.0	65.0	9.74	11.08	11.98	4.50	6.30
MS566PNB472MSZ	4.7±20%	19.1	21.3	30.0	42.0	8.62	9.70	10.42	4.40	6.00
MS566PNB562MSZ	5.6±20%	22.1	24.6	26.0	37.0	7.62	8.74	9.44	3.95	5.75
MS566PNB682MSZ	6.8±20%	24.9	27.7	23.0	33.0	7.38	8.36	9.00	3.70	5.20
MS566PNB822MSZ	8.2±20%	27.4	30.5	22.0	31.0	6.84	7.70	8.32	3.35	4.67
MS566PNB103MSZ	10±20%	36.8	40.9	19.0	27.0	5.88	6.66	7.18	2.85	3.90
MS566PNB123MSZ	12±20%	38.9	43.3	17.0	24.0	5.34	6.04	6.52	2.69	3.65
MS566PNB153MSZ	15±20%	48.6	54.1	15.0	22.0	4.68	5.36	5.78	2.50	3.40
MS566PNB183MSZ	18±20%	51.0	56.7	13.0	19.0	4.32	4.92	5.32	2.41	3.19
MS566PNB223MSZ	22±20%	60.3	67.0	12.6	18.0	3.84	4.34	4.75	2.30	3.14
MS566PNB273MSZ	27±20%	67.5	75.0	11.2	16.0	3.54	4.02	4.32	2.06	2.86
MS566PNB333MSZ	33±20%	81.7	90.8	10.5	15.0	3.24	3.66	3.96	1.90	2.60
MS566PNB393MSZ	39±20%	95.2	105.8	9.3	13.3	3.04	3.46	3.72	1.73	2.39
MS566PNB473MSZ	47±20%	120.6	134.0	8.4	12.0	2.70	3.08	3.34	1.50	2.10
MS566PNB563MSZ	56±20%	133.8	148.7	7.4	10.6	2.46	2.80	3.02	1.44	2.01
MS566PNB683MSZ	68±20%	167.3	185.9	6.8	9.7	2.26	2.54	2.74	1.30	1.80
MS566PNB823MSZ	82±20%	188.5	209.5	6.2	8.8	1.98	2.26	2.46	1.24	1.72
MS566PNB104MSZ	100±20%	216.8	240.9	5.6	8.0	1.84	2.08	2.24	1.19	1.65
MS566PNB124KSZ	120±10%	287.2	319.2	5.0	7.2	1.62	1.86	2.04	1.03	1.42
MS566PNB154KSZ	150±10%	326.7	363.0	4.6	6.6	1.48	1.70	1.82	0.95	1.30
MS566PNB184KSZ	180±10%	379.5	421.7	4.1	5.9	1.36	1.56	1.68	0.89	1.21
MS566PNB224KSZ	220±10%	488.2	542.5	3.7	5.3	1.22	1.38	1.50	0.76	1.00
MS566PNB274KSZ	270±10%	560.1	622.4	3.3	4.7	1.12	1.26	1.36	0.72	0.95
MS566PNB334KSZ	330±10%	731.4	812.7	2.9	4.1	1.00	1.10	1.20	0.65	0.87
MS566PNB394KSZ	390±10%	813.7	904.2	2.7	3.8	0.946	1.00	1.10	0.59	0.79
MS566PNB474KSZ	470±10%	935.1	1039	2.5	3.5	0.864	0.978	1.00	0.56	0.76
MS566PNB564KSZ	560±10%	1193	1326	2.1	3.0	0.776	0.884	0.956	0.50	0.67
MS566PNB684KSZ	680±10%	1370	1523	2.0	2.8	0.720	0.818	0.882	0.46	0.62
MS566PNB824KSZ	820±10%	1590	1767	1.8	2.6	0.634	0.728	0.792	0.43	0.58
MS566PNB105KSZ	1000±10%	2090	2323	1.7	2.4	0.594	0.676	0.728	0.36	0.50

1. When ordering, please specify **testing** code:

**MS566PNB105KSZ**

**Testing:** Z = Unscreened  
H = Group A screening per Coilcraft CP-SA-10001  
T = Screening per MIL-STD-981  
U = Screening per EEE-INST-002  
F = Screening per ESCC 3201  
All screening performed to the document's latest revision  
Custom screening also available

- Inductance measured at 100 kHz, 0.1 Vrms, 0 Adc using a Coilcraft SMD-A fixture in an Agilent/HP 4263B LCR meter or equivalent.
- DCR measured on a micro-ohmmeter and a Coilcraft CCF858 test fixture.
- SRF measured using an Agilent/HP 8753D network analyzer.
- DC current at 25°C that causes the specified inductance drop from its value without current.
- Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings.
- Electrical specifications at 25°C. Refer to Doc 362 "Soldering Surface Mount Components" before soldering.

**Coilcraft CPS**  
CRITICAL PRODUCTS & SERVICES

1102 Silver Lake Road  
Cary, IL 60013  
Phone 800-981-0363


Fax 847-639-1508  
Email cps@coilcraft.com  
www.coilcraft-cps.com

Document MS540-1 Revised 05/30/17






This product may not be used in medical or high risk applications without prior Coilcraft approval. Specifications subject to change without notice. Please check our web site for latest information.

# MS566PNB Series

## Typical L vs Frequency



## Typical L vs Current



\*Dimensions are for the mounted part. Dimensions before mounting can be an additional 0.006 inch (0.152 mm).

### Suggested Land Pattern

Dimensions are in  $\frac{\text{inches}}{\text{mm}}$



1102 Silver Lake Road  
Cary, IL 60013  
Phone 800-981-0363

Fax 847-639-1508  
Email cps@coilcraft.com  
www.coilcraft-cps.com

Document MS540-2 Revised 05/30/17

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specifications subject to change without notice. Please check our web site for latest information.