


Outgassing Compliant Power Inductors AE524PYA



- Exceptionally low DCR; soft saturation
- Passes vibration testing to 80 G and shock testing to 1000 G
- Passes NASA low outgassing specifications
- High temperature materials allow operation in ambient temperatures up to 155°C.
- Tin-lead (Sn-Pb) terminations for the best possible board adhesion

Terminations Tin-lead (63/37) over copper.

Core material Composite

Weight 1.0 – 1.6 g

Ambient temperature –55°C to +105°C with Irms current

Maximum part temperature +155°C (ambient + temp rise).

Storage temperature Component: –55°C to +155°C.

Tape and reel packaging: –55°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Enhanced crush-resistant packaging 250/7" reel

Plastic tape: 16 mm wide, 0.3 mm thick, 12 mm pocket spacing, 3.12 mm pocket depth

Part number ¹	Inductance ² ±20% (µH)	DCR (mOhms) ³		SRF (MHz) ⁴		Isat (A) ⁵	Irms (A) ⁶	
		typ	max	min	typ		20°C rise	40°C rise
AE524PYA681MSZ	0.68	3.10	3.41	47	59	23	14.3	18.8
AE524PYA102MSZ	1.0	3.81	4.19	37	47	21	12.8	17.3
AE524PYA182MSZ	1.8	5.30	5.83	28	36	18.1	10.5	13.5
AE524PYA222MSZ	2.2	6.00	6.60	24	31	16.4	9.8	12.8
AE524PYA302MSZ	3.0	7.45	8.19	20	26	14.6	9.0	12.0
AE524PYA472MSZ	4.7	13.10	14.40	16	21	10.5	5.3	7.5
AE524PYA562MSZ	5.6	14.46	15.90	16	20	9.9	5.3	7.5
AE524PYA682MSZ	6.8	18.90	20.80	14	18	9.2	5.3	6.8
AE524PYA822MSZ	8.2	24.00	26.40	12	16	8.4	4.5	6.0
AE524PYA103MSZ	10	27.00	29.82	11	14	7.6	3.8	5.3
AE524PYA153MSZ	15	39.77	43.75	8.8	11	5.8	3.4	4.5
AE524PYA223MSZ	22	55.12	60.63	7.2	9	5.6	2.7	3.8

1. When ordering, please specify **testing** code:

AE524PYA332MSZ

Testing:

Z = Unscreened

H = Group A screening per Coilcraft CP-SA-10001

All screening performed to the document's latest revision

Custom screening also available

2. Inductance tested at 100 kHz, 0.1 Vrms, 0 Adc.

3. DCR measured on a micro-ohmmeter.

4. SRF measured using an Agilent/HP 4395A or equivalent.

5. DC current at 25°C that causes a 30% (typ) inductance drop from its value without current.

6. Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings.

7. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.













Irms Testing

Irms testing was performed on a 0.060" thick pcb with 4 oz. copper traces optimized to minimize additional temperature rise.

Temperature rise is highly dependent on many factors including pcb land pattern, trace size, and proximity to other components. Therefore temperature rise should be verified in application conditions.

AE524PYA Series

L vs Current



1102 Silver Lake Road
Cary, IL 60013
Phone 800-981-0363

© Coilcraft, Inc. 2018



Fax 847-639-1508
Email cps@coilcraft.com
www.coilcraft-cps.com

Document AE799-2 Revised 09/06/18

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specifications subject to change without notice. Please check our web site for latest information.

AE524PYA Series

L vs Frequency



Dash number	Terminal thickness (typ) (in / mm)
-681	0.0106 / 0.27
-102	0.0106 / 0.27
-182	0.0106 / 0.27
-222	0.0106 / 0.27
-302	0.0106 / 0.27
-472	0.0071 / 0.18
-562	0.0071 / 0.18
-682	0.0059 / 0.15
-822	0.0047 / 0.12
-103	0.0047 / 0.12
-153	0.0039 / 0.10
-223	0.0039 / 0.10

* Height dimension shown is for the mounted part after reflow.
Dimension before mounting can be an additional 0.008 inch / 0.2 mm.

Dimensions are in $\frac{\text{inches}}{\text{mm}}$

Suggested Land Pattern



CRITICAL PRODUCTS & SERVICES
© Coilcraft, Inc. 2018

1102 Silver Lake Road
Cary, IL 60013
Phone 800-981-0363

Fax 847-639-1508
Email cps@coilcraft.com
www.coilcraft-cps.com

Document AE799-3 Revised 09/06/18

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specifications subject to change without notice. Please check our web site for latest information.