

# High Reliability Power Inductors ML619PYA



- High temperature materials allow operation in ambient temperatures up to 155°C
- High current and very low DCR
- Soft saturation makes them ideal for VRM/VRD applications.

**Core material** Composite

**Terminations** Tin-silver over copper.

**Weight** 9.5 – 11.7 g

**Ambient temperature** –55°C to +105°C with Irms current.

**Maximum part temperature** +155°C (ambient + temp rise).

**Storage temperature** Component: –55°C to +155°C.

Tape and reel packaging: –55°C to +80°C

**Resistance to soldering heat** Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

**Moisture Sensitivity Level (MSL)** 1 (unlimited floor life at <30°C / 85% relative humidity)

**Enhanced crush-resistant packaging** 300/13" reel

Plastic tape: 32 mm wide, 0.3 mm thick, 24 mm pocket spacing, 8.26 mm pocket depth

Part number <sup>1</sup>	Inductance <sup>2</sup> ±20% (µH)	DCR (mOhms) <sup>3</sup>		SRF (MHz) <sup>4</sup>		Isat <sup>5</sup> (A)	Irms(A) <sup>6</sup>	
		typ	max	min	typ		20°C rise	40°C rise
ML619PYA401MLZ	0.40	0.50	0.70	42.4	53.0	111	35.3	45.0
ML619PYA741MLZ	0.74	0.72	0.86	28.1	35.1	86.0	32.4	44.8
ML619PYA102MLZ	1.0	0.93	1.12	24.0	30.0	73.5	30.5	43.1
ML619PYA132MLZ	1.3	1.15	1.38	21.0	26.2	65.0	26.0	35.0
ML619PYA182MLZ	1.8	1.61	1.93	17.0	21.3	57.0	24.9	32.9
ML619PYA202MLZ	2.0	1.91	2.29	16.1	20.1	51.0	22.1	29.9
ML619PYA302MLZ	3.0	2.62	3.10	12.8	16.0	43.0	19.2	25.8
ML619PYA452MLZ	4.5	3.82	4.58	10.0	12.5	34.2	15.3	20.3
ML619PYA532MLZ	5.3	4.35	5.22	9.4	11.8	33.0	14.6	19.9
ML619PYA612MLZ	6.1	5.66	6.79	9.4	11.7	31.0	12.7	17.0

1. When ordering, please specify **testing** code:

**ML619PYA822MLZ**

**Testing:** Z = Unscreened  
H = Group A screening per Coilcraft CP-SA-10001  
All screening performed to the document's latest revision

2. Inductance tested at 100 kHz, 0.1 Vrms using an Agilent/HP 4192A.
3. DCR measured using a micro-ohmmeter.
4. SRF measured using an Agilent/HP 4395A or equivalent.
5. DC current at 25°C that causes an inductance drop of 30% (typ) from its value without current.
6. Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings.
7. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.











## Irms Testing

Irms testing was performed on a 0.060" thick pcb with 4 oz. copper traces optimized to minimize additional temperature rise.

Temperature rise is highly dependent on many factors including pcb land pattern, trace size, and proximity to other components. Therefore temperature rise should be verified in application conditions.

# ML619PYA Series (1580)

## L vs Current



1102 Silver Lake Road  
Cary, IL 60013  
Phone 800-981-0363





Fax 847-639-1508  
Email [cps@coilcraft.com](mailto:cps@coilcraft.com)  
[www.coilcraft-cps.com](http://www.coilcraft-cps.com)

Document ML891-2 Revised 07/21/17

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specifications subject to change without notice. Please check our web site for latest information.

# ML619PYA Series (1580)

## Typical L vs Frequency



**Suggested Land Pattern**

Part number	Height max (in / mm)	Terminal thickness typ (in / mm)
619PYA401	0.323 / 8.2	0.0394 / 1.0
619PYA741	0.323 / 8.2	0.0394 / 1.0
619PYA102	0.323 / 8.2	0.0394 / 1.0
619PYA132	0.315 / 8.0	0.0315 / 0.80
619PYA182	0.315 / 8.0	0.0276 / 0.70
619PYA202	0.315 / 8.0	0.0276 / 0.70
619PYA302	0.315 / 8.0	0.0197 / 0.50
619PYA452	0.315 / 8.0	0.0157 / 0.40
619PYA532	0.315 / 8.0	0.0157 / 0.40
619PYA612	0.315 / 8.0	0.0138 / 0.35

Dimensions are in  $\frac{\text{inches}}{\text{mm}}$