

High Reliability Power Inductors MS524PYA



- High temperature materials allow operation in ambient temperatures up to 155°C
- Passes vibration testing to 80 G and shock testing to 1000 G
- Exceptionally low DCR – 3.1 mOhm
- Soft saturation makes them ideal for VRM/VRD applications.

Terminations Tin-lead (63/37) over copper.

Core material Composite

Weight 1.0 – 1.6 g

Ambient temperature –55°C to +105°C with Irms current

Maximum part temperature +155°C (ambient + temp rise).

Storage temperature Component: –55°C to +155°C.

Tape and reel packaging: –55°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Enhanced crush-resistant packaging 250/7" reel

Plastic tape: 16 mm wide, 0.3 mm thick, 12 mm pocket spacing, 3.12 mm pocket depth

Part number ¹	Inductance ² ±20% (µH)	DCR (mOhms) ³		SRF (MHz) ⁴		Isat (A) ⁵	Irms (A) ⁶	
		typ	max	min	typ		20°C rise	40°C rise
MS524PYA681MSZ	0.68	3.10	3.41	47	59	23	14.3	18.8
MS524PYA102MSZ	1.0	3.81	4.19	37	47	21	12.8	17.3
MS524PYA182MSZ	1.8	5.30	5.83	28	36	18.1	10.5	13.5
MS524PYA222MSZ	2.2	6.00	6.60	24	31	16.4	9.8	12.8
MS524PYA302MSZ	3.0	7.45	8.19	20	26	14.6	9.0	12.0
MS524PYA472MSZ	4.7	14.90	16.40	16	21	10.5	5.3	7.5
MS524PYA562MSZ	5.6	16.22	17.84	16	20	9.9	5.3	7.5
MS524PYA682MSZ	6.8	18.90	20.80	14	18	9.2	5.3	6.8
MS524PYA822MSZ	8.2	24.00	26.40	12	16	8.4	4.5	6.0
MS524PYA103MSZ	10	27.00	29.82	11	14	7.6	3.8	5.3
MS524PYA153MSZ	15	39.77	43.75	8.8	11	5.8	3.4	4.5
MS524PYA223MSZ	22	55.12	60.63	7.2	9	5.6	2.7	3.8

1. When ordering, please specify **testing** code:

MS524PYA332MSZ

Testing: Z = Unscreened

H = Group A screening per Coilcraft CP-SA-10001

All screening performed to the document's latest revision

2. Inductance tested at 100 kHz, 0.1 Vrms, 0 Adc.

3. DCR measured on a micro-ohmmeter.

4. SRF measured using an Agilent/HP 4395A or equivalent.

5. DC current at 25°C that causes a 30% (typ) inductance drop from its value without current.

6. Current that causes the specified temperature rise from 25°C ambient. This information is for reference only and does not represent absolute maximum ratings.

7. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.













Irms Testing

Irms testing was performed on a 0.060" thick pcb with 4 oz. copper traces optimized to minimize additional temperature rise.

Temperature rise is highly dependent on many factors including pcb land pattern, trace size, and proximity to other components. Therefore temperature rise should be verified in application conditions.

MS524PYA Series

L vs Current



1102 Silver Lake Road
Cary, IL 60013
Phone 800-981-0363

© Coilcraft, Inc. 2017






Fax 847-639-1508
Email cps@coilcraft.com
www.coilcraft-cps.com

Document MS799-2 Revised 06/02/17

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specifications subject to change without notice. Please check our web site for latest information.

MS524PYA Series

L vs Frequency



Suggested Land Pattern

Dash number	Terminal thickness (typ) (in / mm)
-681	0.0106 / 0.27
-102	0.0106 / 0.27
-182	0.0106 / 0.27
-222	0.0106 / 0.27
-302	0.0106 / 0.27
-472	0.0071 / 0.18
-562	0.0071 / 0.18
-682	0.0059 / 0.15
-822	0.0047 / 0.12
-103	0.0047 / 0.12
-153	0.0039 / 0.10
-223	0.0039 / 0.10

* Height dimension shown is for the mounted part after reflow. Dimension before mounting can be an additional 0.008 inch / 0.2 mm.

Dimensions are in $\frac{\text{inches}}{\text{mm}}$