

# SPICE Model – xx465PYA


This lumped-element (SPICE) model data simulates the frequency-dependent behavior of Coilcraft power inductors within the frequency range shown in the accompanying table for each individual inductor.

The data represents de-embedded measurements, as described below. Effects due to different customer circuit board traces, board materials, ground planes or interactions with other components are not included and can have a significant effect when comparing the simulation to measurements of the inductors using other production verification instruments and fixtures.

## Lumped Element Modeling Method

Measurements were made using a 50 Ohm impedance analyzer. Fixture compensation was performed to remove fixture effects. No DC bias current was applied in any of the measurements. The lumped element values were determined by optimizing the simulation model to an average of the measurements. This method results in a model that represents as closely as possible the typical frequency-dependent behavior of the component within the model frequency range.

The equivalent lumped element model schematic is shown below. Each model should only be analyzed at the input and output ports. Individual elements of the model are not determined by parameter measurement. The elements are determined by the overall performance of the lumped element model compared to the measurements taken of the component.



The value of the frequency-dependent variable resistor  $R_{VAR1}$  is calculated from:

$$R_{VAR1} = k1 * \sqrt{f}$$

- k1 is shown for each value in the accompanying table.
- f is the frequency in Hz
- $R_{VAR1}$  is the resistance in Ohms

The value of the frequency-dependent variable resistor  $R_{VAR2}$  is calculated from:

$$R_{VAR2} = k2 * \sqrt{f}$$

- k2 is shown for each value in the accompanying table.
- f is the frequency in Hz
- $R_{VAR2}$  is the resistance in Ohms

Note: The log function in the following equation is the natural logarithm, base e, not base 10.

The value of the frequency-dependent inductance  $L_{VAR}$  is calculated from:

$$L_{VAR} = k3 - k4 * \text{LOG}(k5 * f)$$

- k3, k4, and k5 are shown in the accompanying table.
- f is the frequency in Hz
- $L_{VAR}$  is the inductance in  $\mu\text{H}$
- LOG is the natural LOG (base e)

## Disclaimer

Coilcraft makes every attempt to provide accurate measurement data and software, representative of our components, in a usable format. Coilcraft, however, disclaims all warrants relating to the use of its data and software, whether expressed or implied, including without limitation any implied warranties of merchantability or fitness for a particular purpose. Coilcraft cannot and will not be liable for any special, incidental, consequential, indirect or similar damages occurring with the use of the data and/or software.

# SPICE Model for Coilcraft xx465PYA Power Inductors

Part number	Frequency limit of model (MHz)		R1 ( $\Omega$ )	R2 ( $\Omega$ )	C (pF)	k1	k2	L <sub>VAR</sub> Coefficients		
	Lower	Upper						k3	k4	k5
xx465PYA521	0.1	200	20	0.00483	3.69	6.00E-05	0.0470	0.52	0.004	7.00E-06
xx465PYA681	0.1	200	26	0.00574	4.00	1.40E-04	0.0680	0.68	0.005	5.00E-06
xx465PYA821	0.1	200	20	0.00665	4.65	1.10E-04	0.0900	0.82	0.010	5.00E-06
xx465PYA102	0.1	200	20	0.00754	4.66	1.10E-04	0.110	1.0	0.014	8.50E-06
xx465PYA152	0.1	100	35	0.0103	4.98	5.00E-05	0.190	1.5	0.018	9.50E-06
xx465PYA222	0.1	100	30	0.0152	4.99	1.80E-04	0.260	2.2	0.024	8.50E-06
xx465PYA332	0.1	80	30	0.0265	5.35	2.80E-04	0.410	3.3	0.030	8.50E-06
xx465PYA472	0.1	70	30	0.0337	4.84	3.00E-04	0.650	4.7	0.046	9.00E-06
xx465PYA682	0.1	50	30	0.0449	5.97	4.00E-04	0.900	6.8	0.080	9.10E-06
xx465PYA822	0.1	40	35	0.0608	5.72	1.00E-04	1.15	8.2	0.090	9.70E-06
xx465PYA103	0.1	40	35	0.0840	5.71	1.50E-04	1.30	10	0.10	9.60E-06
xx465PYA153	0.1	30	35	0.109	5.61	1.00E-04	1.90	15	0.11	9.60E-06



CRITICAL PRODUCTS & SERVICES

© Coilcraft, Inc. 2012

1102 Silver Lake Road  
Cary, IL 60013  
Phone 800-981-0363

Fax 847-639-1508  
Email [cps@coilcraft.com](mailto:cps@coilcraft.com)  
[www.coilcraft-cps.com](http://www.coilcraft-cps.com)

Document 267C-100 Revised 11/30/12

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specifications subject to change without notice. Please check our web site for latest information.